



Material Safety Data Sheet

NFPA	PPE		

Issued Date 22-Oct-2008

Revision Date 14-Jan-2009

Revision Number: 5

24-V7 - Solutec Vector 7

1. PRODUCT AND COMPANY IDENTIFICATION

DECCO
 Cerexagri, Inc.
 1713 S. California Ave.
 Monrovia, CA 91016-0120

Emergency Telephone Number
 Chemtrec: (800) 424-9300 (24hrs) or (703) 527-3887
 Medical: Rocky Mountain Poison Control Center
 (866) 673-6671 (24hrs)

Company Information
 Decco-Cerexagri

Contact Information
 Customer Service

Phone Number
 626-358-1838

Available Hrs
 8:00am - 5:00pm (PT)

Product Name Solutec Vector 7
Recommended Use Apple wax coating
Product Code 24-V7

2. HAZARDS IDENTIFICATION

Emergency Overview		
Flammable Liquid Irritating to eyes Irritating to skin		
Vapors may travel along ground and ignite by ignition sources distant from the handling point.		
WARNING!		
Appearance Clear, Amber.	Physical State Liquid.	Odor Alcohol odor.

Potential Health Effects

- Inhalation
 - Skin contact
- Acute Effects**

Inhalation and skin contact are expected to be the primary routes of exposure to this material. Based on single exposure animal tests, it is considered to be slightly toxic to practically non-toxic if swallowed, practically non-toxic if absorbed through skin or inhaled, moderately irritating to the eyes and slightly irritating to the skin. Prolonged or repeated contact may remove oils from the skin and cause irritation, redness and rash. High vapor concentrations may be irritating to the eyes and respiratory tract, and may result in central nervous system (CNS) effects such as headache, dizziness, nausea, drowsiness and, in severe exposure loss of consciousness. If swallowed, this material may cause digestive tract irritation, vomiting and CNS effects as noted above. Mild to severe lung injury may occur if this material is drawn into the lungs (aspirated) during swallowing, or during vomiting after swallowing. SYMptoms may include increased breathing and heart rate, coughing and related signs of respiratory distress.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients Name

Chemical Name	CAS-No	Weight %	OSHA PEL
Morpholine oleate	1095-66-5	4.25	N/A
Isopropanol	67-63-0	20	980 mg/m ³ 400 ppm

4. FIRST AID MEASURES

Eye Contact	Hold eye open and rinse slowly and gently with water for 15 - 20 minutes. Remove contact lenses, if present, after 5 minutes, then continue rinsing eye. If symptoms persist, call a physician
Skin Contact	Wash off with warm water and soap If symptoms persist, call a physician
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration. Call a poison control center or doctor for further treatment advice.
Ingestion	Do not induce vomiting unless told to do so by a poison control center or doctor Never give anything by mouth to an unconscious person Have person sip a glass of water if able to swallow Call a physician or poison control center for treatment advice.
Notes to Physician	No information available

5. FIRE-FIGHTING MEASURES

Flammable Explosive Properties

Flash Point	84-86°F
Method	Closed cup
Autoignition Temperature	Not available

Flammability Limits in Air Not available

Extnguishing Media Use: Carbon dioxide (CO2) Dry chemical Foam

Fire/Explosion Hazard Firefighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear and self-contained breathing apparatus. Fire fighting equipment should be thoroughly decontaminated after use. Flammable Keep product and empty container away from heat and sources of ignition Flash back possible over considerable distance

Hazardous Combustion Products Carbon monoxide, Oxides of nitrogen.

NFPA **Health 2** **Flammability 3** **Instability 0**

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Remove all sources of ignition. Ensure adequate ventilation. Use personal protective

equipment. Avoid contact with skin, eyes and clothing.

Environmental Precautions

Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits..

Methods for Clean-up

Remove all ignition sources. Use non-sparking tools . Ground and bond containers when transferring material. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flame. - No smoking. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Do not eat, drink or smoke when using this product. Keep out of reach of children. Check that all equipment is properly bonded and grounded..

Storage

Keep in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Protect from sunlight and store in well-ventilated place. Static electricity may accumulate when transferring material. All containers must be bonded and grounded during filling and emptying operations..

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL
Isopropanol	200 ppm	980 mg/m ³ 400 ppm

Engineering Controls

Investigate engineering techniques to reduce exposures. Local mechanical exhaust ventilation is preferred. Consult ACGIH ventilation manual or NFPA Standard 91 for design of exhaust systems. .

Personal Protective Equipment**Eye/face Protection**

Avoid contact with eyes. Goggles.

Skin Protection

Rubber gloves. Wear protective gloves/clothing.

Respiratory Protection

Where airborne exposure is likely, use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. If exposures cannot be kept at a minimum with engineering controls, consult respirator manufacturer to determine appropriate type equipment for given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure, use an approved full face positive-pressure, self-contained breathing apparatus. Respiratory protection programs must comply with 29 CFR 1910.134. .

General Hygiene Considerations

Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear Amber	Odor	Alcohol odor
Physical State	Liquid	pH	approx.8.5
Boiling Point/Range	82°C	Melting Point/Range	Not available
Specific Gravity	0..995	Solubility	Soluble
Evaporation Rate	Not available	Vapor Pressure	Not available
Vapor Density	Not available	VOC Content	Not available
Viscosity	22 (+/-5) cps	Molecular Weight	No data available
Bulk Density	8.30 lb/gal	Percent Solids	20%
Percent Volatiles	80%		

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions
Conditions to Avoid	Heat, flames and sparks. Extremes of temperature and direct sunlight. Keep away from children.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	No information available.
Possibility of Hazardous Polymerization	Hazardous polymerisation does not occur

11. TOXICOLOGICAL INFORMATION**Acute Toxicity****Component Information****Isopropanol:**

No skin irritation was reported in humans following a single 24 hour exposure. Low doses (2.6 and 6.4 mg) given daily to human volunteers orally for 6 weeks was without adverse effects on the blood. Signs of toxicity in rodents following single oral or inhalation exposures included sensory irritation, liver effects, narcosis and CNS depression. Skin irritation and injury were observed in rabbits following repeated skin application, while sensory irritation, liver and kidney changes and narcosis were observed in rats and mice following repeated inhalation. No signs of nervous system toxicity were observed in rats or mice following repeated inhalation in rats following repeated administration in drinking water. No adverse effects were observed in dogs following repeated administration in drinking, while a decrease in body weight gain was the only adverse effect reported in rats. Long-term skin application produced no skin tumors in mice. No increase in lung tumors occurred in mice after long-term inhalation. No signs of neurotoxicity or developmental toxicity were noted in the offspring of rats exposed orally during pregnancy. No birth defects were noted in the offspring of rats and rabbits exposed orally during pregnancy, even at amounts which produced toxic effects in the mothers and offspring. Birth defects were reported in the offspring of rats exposed by inhalation during pregnancy, but only at levels which produced significant adverse effects on the mothers. No genetic changes were observed in tests using bacteria or animal cells or animals.

Single exposure studies indicate that this material is slightly to practically non-toxic if swallowed (rat LD50 4,475-7,990 mg/kg) practically non-toxic if absorbed through the skin (rabbit LD50 6,300-13,000 mg/kg) or inhaled (rat 8 hr LC50 51 mg/l), moderately irritating to rabbit eyes (15.8-27/110) and slightly irritating to rabbit skin (4 hr exposure 2/8)

Morpholine oleate:

No toxic or carcinogenic effects were observed in mice following repeated exposure in their drinking water.

Chronic Toxicity

There are no known carcinogenic chemicals in this product

Carcinogenicity**12. ECOLOGICAL INFORMATION**

Ecotoxicity

Isopropanol:

This material is practically non-toxic to *Daphnia magna* (48 hr ec50 2,285 mg/l), fruit fly (48 hr - LC50 10,200 mg/l), fathead minnow (96 hr LC50 3,200-9,640 mg/l), brown shrimp (96 hr LC50 1,150 mg/l), rainbow trout (96 hr LC50 7,600 mg/l), sheephead minnow (96 hr LC50 12,100 mg/l) and mysid shrimp (96 hr LC50 4,050 mg/l).

Chem Fate:

This material will rapidly photooxidize in the atmosphere. It has been shown to be rapidly biodegradable in adapted activated sludge and fresh and salt waste water dilutions (5 day BOD in adapted sludge 99%, 20-day BOD in unadapted sludge 70-78% in fresh water and 72% in salt water). The log Pow is 0.14.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with local regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. Do not apply directly to wetlands or water..

Contaminated Packaging

Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT

Not regulated as per 173.150 (e) of 49 CFR. When shipped domestically by highway in non-bulk containers this product can be shipped as not regulated.

ICAO

UN-No	1866
Proper Shipping Name	Resin solution
Hazard Class	3
Packing Group	PG III

IATA

UN-No	1866
Proper Shipping Name	Resin solution
Hazard Class	3
Packing Group	PG III
ERG Code	3 L

IMDG/IMO

Proper Shipping Name	Resin solution
Hazard Class	3
UN-No	1866
Packing Group	PG III
EmS No.	F-E, S-E

15. REGULATORY INFORMATION

International Inventories

Morpholine oleate

DSL	Listed
EINECS/ELINCS	Listed
CHINA	Listed
KECL	Listed

Isopropanol

DSL	Listed
EINECS/ELINCS	Listed
ENCS	Listed
CHINA	Listed
KECL	Listed

USA

Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Chemical Name	CAS-No	Weight %	HAPS data	VOC Chemicals	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Isopropanol	67-63-0	20		Listed.		

CERCLA

Chemical Name	RQ
Isopropanol	Listed.

RCRA**Pesticide Information****State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropanol	Listed.		Listed.	Listed.	Listed.

International Regulations**Mexico - Grade**

Mexico - Grade

Chemical Name	Category	Carcinogen Status	Exposure Limits
Isopropanol			980 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Not determined

Chemical Name	NPRI
Isopropanol	X

16. OTHER INFORMATION

Revision Date

14-Jan-2009

Revision Summary

Update section 15

UPI, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with other materials or in any process. Further, since the conditions and methods of use are beyond the control of UPI, Inc. UPI, Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

End of MSDS